



## **EXPECT QUALITY AND RELIABILITY**

using our brand name WC T50 REGULATOR

Version 4.0



## **Head Office:**



7596 Wagner RD NW Edmonton , Alberta CANADA T6E 5B2 info@weirusa.com / www.weirusa.com

1.866.462.1910 Toll Free

780.462.1910 ph | 780.462.1959 fax

**DOMESTIC PRODUCTS MADE IN NORTH AMERICA** 

Details are the difference between ordinary and EXCELLENCE





#### **T50 REGULATOR**

This product is designed for instrumentation and general purpose application. Made of die-cast aluminum housing and finished with vinyl paint for resistance to scratching and weathering. The rubberized, soft seat valve stem provides positive shut off and tolerates dirt or other foreign matter.

#### **FEATURING**

- Superior regulation characteristics
- Rugged, corrosion resistant
- Excellent stability and repeatability
- Self relieving
- Integral, 40 micro self cleaning full mesh filter
- Low droop at high flow
- Several mounting options

#### **APPLICATION**

The design of the T50 regulator is suited to pilot operated controllers, instruments, and applications like actuators, air chucks, air spray guns, and air cylinders.

## **Weir USA at work for you**

The T50 regulator aspirator maintains downstream pressure and compensates for droop when high flow occurs. The full flow gauge port is convenient for installation and can also be used as an additional full flow outlet.

#### Sensitivity

1" (25.4mm) water column

#### Flow capacity

20 SCFM (565 LPM)

Effect of supply pressure variation (25 psi) on outlet pressure

<0.2 psi (0.01 BAR)

**Exhaust capacity** 

(5 psi above 20 psi set point)

0.1-0.45 SCFM typical (2.8-12.7 LPM)

Maximum input/supply pressure

250 psi (17.2 BAR)

Effect of changes in flow on regulated pressure (100 psi/6.9 BAR supply)

4 psi (0.3 BAR) overflow 10 SCFM (283 LPM) (1/4" NPT, 20 psi / 1.4 BAR set point)

#### **Output pressure ranges**

0-10 psi (0-0.7 BAR), 0-30 psi (0-2.1 BAR) 0-60 psi (0-4.1 BAR), 0-120 psi (0-8.3 BAR)

**Temperature ranges** 

-47 to 176F

Total air consumption @ maximum output

6 SCFH (2.8 LPM)

#### Port size

1/4" NPT, BSPT

Size

3.19" X 3.19" X 7.25" 81 X 81 X 184mm)

Weight

1.81 lb. (0.8kg)

#### **Materials of construction**


**Body**: die-cast aluminum c/w vinyl paint

Adjusting Screw: plated steel

**Trim**: plated steel, brass, acetal resin


**Diaphragm:** Buna-N elastomeric with polyester fabric


Knob: Plastic



# **PRODUCT GUIDE**

### **WEIR WC T50 REGULATOR**









# **SOLUTIONS FOR YOUR COMPANY NEEDS - WORLD WIDE SHIPPING**



- HELP DESK -

FOR YOUR SUPPORT AND SERVICE

24 hours a day, 7 days a week NO CHARGE ON CALLS SERVICE

We offer technical assistance, product knowledge, and reliable trouble shooting

Brochures/Maintenance info available online www.weirusa.com



## **Head Office:**

7596 Wagner RD NW Edmonton, Alberta CANADA T6E 5B2 info@weirusa.com / www.weirusa.com

**1.866.462.1910 Toll Free** 780.462.1910 ph | 780.462.1959 fax